



MONIMET

O₂-Sensor/transmitter type GMM 02.15.xxx

O₂-Monitor type GMM 02.15.xxx

- I M1 Ex ia I Ma
- Linearized measured value display from 0.00...30.00 % O₂
- Electrochemical measurement process with gas diffusion entry
- Increased accuracy by compensation of prevailing air-pressure and temperature by microcontroller
- Version for gas exhaustion pipes and pipelines
- Special housing suited to the working conditions in mines and industry
- Pipe probe type RSM 01.xx with test gas connection (optional)
- Illuminated four-digit display
- Output range of the output signal is variable
- Adjustments or status enquiries by means of a press button unit or a magnetic pointer. The housing need not be opened
- Code lock to prevent unauthorized manipulation (can be switched off)
- Fault self diagnosis with alpha numeric display
- Test of the output signal by simulated gas values
- Choice between normed analog or digital output signals (optional)
- Two built-in limit switches with optocouplers or relays in the monitor
- Housing protection rating IP65, sensor protection rating IP 54

The economical, permanently installed O₂-Sensor/transmitter and O₂-Monitor are characterised by their stable measurements, simple and secure operation, robustness, and compact construction.

These devices conform to the explosion protection rating of intrinsic safety „i“, category I M1 Ex ia I Ma. This means that this device can be used in the zone M1 of underground mines, even when unpermitted high concentrations of the methane gas are prevailing.

This certification conforms to the ATEX directive 2014/34/EU for devices and protective systems permitted for use in areas endangered by explosions.

The O₂-Monitor differs from the O₂-Sensor/transmitter because of an additional limit value unit which is equipped with optocouplers or relays.

The measurement of the oxygen concentration in the sensor block is by means of an electrochemical sensor. The gas diffuses into the measuring chamber through a sinter metal disc.

To increase the measurement accuracy, a microcontroller continuously compensates the prevailing temperature and air-pressure values.

The gas supply from the suction pipe is achieved by an pipe probe type RSM 01.xx. The pipe probe contains a dust filter and a connection for the test gases.

The operation of the device is very simple: The operator places a small magnetic press button unit on the device. The housing need not be opened. As an alternative he can also use a magnetic pointer. A four digit code which can be entered initially, protects against unauthorized changing of the set values.

A self monitoring microcontroller system not only processes the measurement values precisely, it also carries out the operator specific instructions such as the entry of the code, signal instructions and messages, analog and digital outputs and test functions etc. A four digit back lit graphic display shows the measured values in 12 mm high digits.

These devices are protected against shocks, dust and humidity by a cast metal housing (impact strength 20 Joule) and are to be connected by means of a plug-in connector. The sensor block with the O₂-sensor is attached on the lower side of the housing and it can be replaced easily on the underground site.

The adapter can be used for the mounting of the device. Alternatively, a steel hanger or thread holes on its rear side can also be used for the mounting.

MONIMET
O₂-Sensor/transmitter type GMM 02.15.xxx
O₂-Monitor type GMM 02.15.xxx

Technical Data

Certification	 DMT 03 ATEX E 065 X according to directive 2014/34/EU
Zone, Explosion protection rating	 I M1 Ex ia I Ma
Principle of measurement	Electrochemical cell
Gas entry	Diffusion
Range of measurement	0.00...30.00% O₂ (V/V)
Error of measurement:	2% of the final value of the measurement range
Influence of temperature, humidity and pressure	fulfils EN 50104
Maximum permitted concentration	100% O ₂
Resolution	0.01% O ₂
Measured value response time t ₉₀	≤ 30 s with input filter
Display sequence	0.5 s
Run in time	1 Minute
Adjustment range of the device code	0000...9999
Supply voltage	9...16 V–
Current consumption	
Sensor/transmitter with 1 mA- or 15 Hz output	15 mA
Sensor/transmitter with 20 mA output	35 mA
Monitor with Optocouplers and 1 mA- or 15 Hz output	17 mA
Monitor with relays and 1 mA- or 15 Hz output	27 mA
Monitor with Optocouplers and 20 mA output	37 mA
Monitor with relays and 20 mA output	47 mA
Frequency output	
Frequency range	6...15 Hz, switchable to 5...15 Hz
Output range adjustable between	1...100% O ₂
Optocoupler output	max.: 30 V, 100 mA, 100 mW
Current output (alternative to the frequency output)	
Ranges and loads	0.1/0.2...1 mA / ≤5200 Ω to 4...20 mA / ≤200 Ω
Output range adjustable between	1...100% O ₂
Test function by simulated measured values	10 decimal steps from 0 ppm O ₂ to the final value of the range of the data transmission output
Limit switch Alarm 1 and Alarm 2 (Monitor)	
Setting range	0.01...30.00% O ₂
Optocoupler output (quiescent current principle)	max. 30 V, 100 mA, 100 mW
Relay output (quiescent current principle)	max. 30 V, 1 A, 30 W
Surroundings temperature	-20°C...+50°C
Humidity	15... 95% rel., short-term 0...98% rel.
Dimensions without hanger	W 100 mm, D 100 mm, H 180 mm
Weight without alarm unit	4 kg
Type of protection	IP 65, Gas inlet port IP 54
Material / varnish paint	Die cast metal / RAL 5012 (blue)
Impact strength	20 Joule
Accessories to be ordered separately	
Connecting cable	VDL 4, 20m, max. length 100 m (R _L ≤ 7,8 Ω)
Input filter	STF 3
Test gas set	PGS 3
Press button device	TAS 3
Pipe probe, 90 mm	RSM 01.90
Pipe probe, 160 mm	RSM 01.160
Subject to technical updates	

22-11